# NSN 5930-00-498-5600

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-498-5600

# Thread Class:

2a single mounting facility

# Thread Length:

0.437 inches single mounting facility

# Hazardous Locations/environmental Protection:

Explosion proof

#### **Overall Length:**

1.899 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.874 inches single actuator

# **Overall Diameter:**

1.306 inches

# Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

# Operating Tempurature Range:

-65.0/+85.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 single section front

# Throw Quantity:

4 single section front

# **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# Contact Voltage Rating In Volts:

28.0 dc at sea level

# Shaft Flat/slot Angular Location:

190.0 degrees from nonturn device single actuator

# Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

# NSN 5930-00-498-5600

Rotary Switch - Page 2 of 2



Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

# **Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

#### Style Designator:

Tap, circular, bushing mount

#### **Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

--Demilitarization: No

Fiig:

A052b0