

View Online at <https://aerobasegroup.com/nsn/5930-00-498-5895>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.690 inches

Overall Height:

0.926 inches

Body Diameter:

1.187 inches

Mounting Slot Width:

0.176 inches

Body Height:

0.464 inches

Distance Between Mounting Facility Centers:

Between 1.375 inches and 1.405 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

60.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

85.00 actuation point degrees celsius and 95.00 actuation point degrees celsius and 56.00 deactuation point degrees celsius and 66.00 deactuation point degrees celsius and 29.00 differential point degrees celsius

Contact Voltage Rating In Volts:

200.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0