

View Online at <https://aerobasegroup.com/nsn/5930-00-498-6783>

First Flat Length:

0.625 inches single actuator

Flat Height:

0.156 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.703 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section front

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

220.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0