

View Online at <https://aerobasegroup.com/nsn/5930-00-498-8420>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof and sand proof

**Overall Length:**

Between 0.484 inches and 0.516 inches

**Overall Height:**

Between 1.030 inches and 1.126 inches

**Overall Width:**

Between 0.374 inches and 0.438 inches

**Body Length:**

0.500 inches

**Body Width:**

0.250 inches

**Body Height:**

Between 0.546 inches and 0.610 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

Between 0.484 inches and 0.516 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0