

View Online at <https://aerobasegroup.com/nsn/5930-00-498-8496>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof and sand proof

**Overall Length:**

Between 1.250 inches and 1.312 inches

**Overall Height:**

0.344 inches

**Overall Width:**

0.344 inches

**Body Diameter:**

0.344 inches

**Bushing Length:**

0.281 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.109 inches

**Actuator Height:**

0.328 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

110.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.672 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Rfi shielding

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.500 amperes resistive dc and 500.000 milliamperes inductive dc and 500.000 milliamperes lamp dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac and 500.000 milliamperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0