

View Online at <https://aerobasegroup.com/nsn/5930-00-498-8496>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof and sand proof

Overall Length:

Between 1.250 inches and 1.312 inches

Overall Height:

0.344 inches

Overall Width:

0.344 inches

Body Diameter:

0.344 inches

Bushing Length:

0.281 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.109 inches

Actuator Height:

0.328 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

110.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.672 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc and 500.000 milliamperes inductive dc and 500.000 milliamperes lamp dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac and 500.000 milliamperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0