

View Online at <https://aerobasegroup.com/nsn/5930-00-499-2033>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

7.644 inches

Overall Height:

2.312 inches

Overall Width:

1.968 inches

Shaft Diameter:

0.375 inches 1st actuator

Shaft Length:

0.938 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 10: 00 o'clock

Individual Section Quantity:

7

Nonturn Device Type:

Tab at 10: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.625 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

24 2nd actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

15.0 degrees 2nd actuator

Detent Rotational Torque Range:

+30.000/+45.000 inch-ounces all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Clips and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0