## NSN 5930-00-499-2034

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-499-2034

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

11.603 inches

**Shaft Diameter:** 

0.250 inches 1st actuator

**Shaft Length:** 

9.468 inches 1st actuator

**Overall Diameter:** 

1.250 inches

**Nonturn Device Radius:** 

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

5 1st actuator

**Shaft Type:** 

Round, hollowed 1st actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

60.0 degrees 2nd actuator

**Detent Rotational Torque Range:** 

+15.000/+30.000 inch-ounces 2nd actuator

**Switch Actuator Stop Device Type:** 

Fixed stop all actuators

**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Clips and @rotor blades silver

## NSN 5930-00-499-2034

Rotary Switch - Page 2 of 2



Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0