

View Online at <https://aerobasegroup.com/nsn/5930-00-499-2184>

Hazardous Locations/environmental Protection:

Explosion proof and moisture resistant and salt spray resistant

Overall Length:

2.250 inches

Overall Height:

1.705 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.094 inches single mounting facility

Distance Between Mounting Facility Centers:

0.968 inches single mounting facility

Individual Section Quantity:

4

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Features Provided:

Illuminated

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 1st actuator

Terminal Type:

Tab, solder lug and wire loop

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

N, s 1st section

Contact Arrangement Truth Table:

Special 1st section

Special Truth Table Identification:

88818-special 0-1 1st section

Color:

White each indicator marking

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0