# NSN 5930-00-499-7389

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-499-7389

Body Style:					
Bushing mount					
Hazardous Locations/environmental Protection:					
Weatherproof					
Overall Length:					
1.340 inches					
Overall Height:					
2.980 inches					
Overall Width:					
0.910 inches					
Bushing Length:					
0.470 inches					
Body Length:					
1.340 inches					
Body Width:					
0.910 inches					
Body Height:					
1.100 inches					
Actuator Style:					
Round					
Actuator Diameter:					
0.420 inches					
Actuator Height:					
1.140 inches					
Actuator Position-action Relationship:					
Up position maintained and down position maintained and center position maintained					
Actuator Position-locking Relationship:					
Up position locked in and down position locked in and center position locked in					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
End Application:					
Helicopter iroquis uh-1/mrap rg 31					
Mounting Surface To Terminal End Distance:					
1.370 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Threaded bushing					
Features Provided:					
Actuator seal					
Thready Qty Per Inch (tpi):					

32

# NSN 5930-00-499-7389

Toggle Switch - Page 2 of 2



_				•	
	n	rea	а	~	70.

0.469 inches

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

# **Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

#### **Precious Material And Location:**

Terminal surfaces silver

#### **Test Data Document:**

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Uns

# **Terminal Type And Quantity:**

6 screw

#### **Specification Data:**

96906-ms24659 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

# **Demilitarization:**

No

Fiig:

A053a0