

View Online at <https://aerobasegroup.com/nsn/5930-00-501-0006>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant

Overall Length:

0.780 inches

Overall Height:

1.480 inches

Overall Width:

0.906 inches

Bushing Length:

0.310 inches

Body Length:

0.780 inches

Body Width:

0.906 inches

Body Height:

1.480 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.323 inches

Actuator Height:

0.190 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Aircraft, stratolifter c-135, delta dart f-106, galaxy c-5, awacs e-3a; support equipment, t-37 aircraft, t-38 aircraft

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Four flexible insulators; weapon system essential

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0