## NSN 5930-00-501-0101

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-0101

g
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
0.796 inches
Overall Height:
1.656 inches
Overall Width:
0.656 inches
Bushing Length:
0.312 inches
Body Length:
0.796 inches
Body Width:
0.656 inches
Body Height:
1.031 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
Between 0.405 inches and 0.435 inches
Actuator Height:
0.438 inches
Maximum Voltage Rating In Volts:
250.0 ac and 125.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

30.0 ounces

## NSN 5930-00-501-0101

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.040 pretravel inches and 0.105 overtravel inches and 0.050 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 250.000 milliamperes inductive dc and 5.000 amperes resistive ac

**Special Features:** 

Black plastic push button

**Precious Material And Location:** 

Contacts silver

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0