NSN 5930-00-501-0992

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-0992
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Vaportight
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.860 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.152 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.280 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.190 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
Between 9.0 ounces and 21.0 ounces
Actuator Movement:
Between 0.080 pretravel inches and 0.020 overtravel inches and 0.040 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
25,000 amperes resistive dc and 10,000 amperes inductive dc and 1,000 amperes resistive ac and 1,000 amperes inductive ac

3 screw

Terminal Type And Quantity:

NSN 5930-00-501-0992

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0