

View Online at <https://aerobasegroup.com/nsn/5930-00-501-1185>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.000 inches

Overall Width:

0.688 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.875 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.125 inches

Actuator Width:

0.297 inches

Actuator Free Position Height:

0.505 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

Between 23.0 ounces and 33.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.180 overtravel inches and 0.280 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes inductive dc and 15.000 amperes resistive ac

Special Features:

Terminals epoxy resin sealed

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0