

View Online at <https://aerobasegroup.com/nsn/5930-00-501-1250>

Thread Class:

2a single mounting facility

Thread Length:

0.296 inches single mounting facility and 0.328 inches single mounting facility

Width Between Flats:

0.186 inches single actuator and 0.188 inches single actuator

Overall Length:

2.297 inches

Overall Height:

1.953 inches

Overall Width:

1.797 inches

First Flat Length:

0.125 inches single actuator and 0.157 inches single actuator

Shaft Diameter:

0.531 inches single actuator and 0.558 inches single actuator

Shaft Length:

0.531 inches single actuator and 0.558 inches single actuator

Nonturn Device Radius:

0.515 inches at 4: 30 o'clock and 0.547 inches at 4: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 4: 30 o'clock

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

32.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0