Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-1270

| Hazardous Locations/environmental Protection: |
|-------------------------------------------------------|
| Dustproof |
| Overall Height: |
| 2.719 inches |
| Overall Width: |
| 2.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.257 inches single mounting facility |
| Individual Section Quantity: |
| 4 |
| Longest Horizontal Distance Between Mounting Centers: |
| 3.500 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section front |
| Throw Quantity: |
| 1 each section front |
| Mounting Method: |
| Base single mounting facility |
| Contact Voltage Rating In Volts: |
| 500.0 ac at sea level |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Shaft Type: |
| Rectangular/square, threaded hole single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 60.0 degrees single actuator |
| Contact Load Current Rating: |
| 3.0 amperes resistive load dc at sea level |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

No

NSN 5930-00-501-1270 Rotary Switch - Page 2 of 2

Fiig: A052b0

