

View Online at <https://aerobasegroup.com/nsn/5930-00-501-1326>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.188 inches

Body Diameter:

0.618 mils and 0.625 centimeters

Body Length:

3.562 inches

Overall Diameter:

1.250 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Facility Circle Radius:

0.625 inches

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 1000.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+300.00 actuation point degrees fahrenheit and -100.00/+300.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

0.00 actuation point degrees fahrenheit and 120.00 actuation point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0