NSN 5930-00-501-1554

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-1554

Hazardous Locations/environmental Protection:			
Dustproof			
Overall Length:			
5.250 inches			
Overall Height:			
3.688 inches			
Overall Width:			
3.375 inches			
Shaft Diameter:			
0.250 inches single actuator			
Shaft Length:			
1.000 inches single actuator			
Individual Section Quantity:			
8			
Longest Horizontal Distance Between Mounting Centers:			
1.641 inches single mounting facility			
Longest Vertical Distance Between Mounting Centers:			
1.641 inches single mounting facility			
Switch Contact Basic Design:			
Nonpile-up nonsymmetrical			
Mounting Method:			
Bracket single mounting facility			
Features Provided:			
Actuator knob			
Thready Qty Per Inch (tpi):			
24 single mounting facility			
Thread Size:			
0.190 inches single mounting facility			
Contact Voltage Rating In Volts:			
450.0 highest ac voltage rating at sea level			
Mounting Facility Pattern:			
Four position rectangular single mounting facility			
Switch Actuator Indexing Position Quantity:			
4 single actuator			
Shaft Type:			
Round, hollowed single actuator			
Terminal Type:			
Tab w/screw			
Contact Switching Action:			
$\label{eq:makes} \mbox{ Makes before breaks, breaks before makes each section front }$			
Switch Actuator Positioning Increment:			

90.0 degrees single actuator

NSN 5930-00-501-1554

Rotary Switch - Page 2 of 2



Contact	I oad	Current	Rating:
Cullact	Luau	Current	mauniu.

10.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0