NSN 5930-00-501-1631

Sensitive Switch - Page 1 of 2

9.5 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-501-1631

| Body Style: |
|---|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 1.938 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Overall Height: |
| 1.360 inches |
| Overall Width: |
| 0.688 inches |
| Body Length: |
| 1.938 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 0.844 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.156 inches |
| Actuator Height: |
| 0.266 inches |
| Actuator Free Position Height: |
| 1.110 inches |
| Maximum Voltage Rating In Volts: |
| 460.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |

NSN 5930-00-501-1631

Sensitive Switch - Page 2 of 2



| Δ | ctu | ato | - М | ΛV/ | am. | ۵ni | ŀ |
|---|-----|-----|-----|-----|------|-----|----|
| н | CLU | alu | IVI | OVE | 2111 | | L. |

Between 0.012 pretravel inches and 0.062 overtravel inches and 0.0004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A053a0