NSN 5930-00-501-1631

Sensitive Switch - Page 1 of 2

9.5 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-501-1631

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.938 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.360 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.844 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.156 inches
Actuator Height:
0.266 inches
Actuator Free Position Height:
1.110 inches
Maximum Voltage Rating In Volts:
460.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

NSN 5930-00-501-1631

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	am.	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

Between 0.012 pretravel inches and 0.062 overtravel inches and 0.0004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

Unit Of Measure:

N/a

Demilitarization:

No

Fiig:

A053a0