NSN 5930-00-501-1770

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-1770

| Hazardous Locations/environmental Protection: | | | | | |
|--|--|--|--|--|--|
| Dustproof and watertight | | | | | |
| Switch Actuator Quantity: | | | | | |
| 1 | | | | | |
| Actuator Style: | | | | | |
| Round | | | | | |
| Actuator Height: | | | | | |
| 1.000 inches | | | | | |
| Actuator Free Position Height: | | | | | |
| 2.188 inches | | | | | |
| Housing Height: | | | | | |
| 2.156 inches | | | | | |
| Housing Length: | | | | | |
| 4.000 inches | | | | | |
| Housing Width: | | | | | |
| 1.156 inches | | | | | |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Height: | | | | | |
| 1.625 inches | | | | | |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: | | | | | |
| 3.500 inches | | | | | |
| Maximum Voltage Rating In Volts: | | | | | |
| 230.0 dc | | | | | |
| Inclosure Type: | | | | | |
| Fully enclosed | | | | | |
| Features Provided: | | | | | |
| Actuator seal | | | | | |
| Nonpile-up Contact Arrangement: | | | | | |
| 1 pole, double throw, one position momentary single switch unit | | | | | |
| Switch Release Force: | | | | | |
| 8.0 ounces | | | | | |
| Switch Actuating Force: | | | | | |
| 40.0 ounces | | | | | |
| Actuator Movement: | | | | | |
| Between 0.094 pretravel inches and 0.219 overtravel inches and 0.005 differential inches | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | |
| 5.000 amperes resistive dc | | | | | |
| Special Features: | | | | | |
| 3 mtg holes | | | | | |
| Terminal Type And Quantity: | | | | | |
| 3 screw | | | | | |
| Shelf Life: | | | | | |

N/a

NSN 5930-00-501-1770

Sensitive Switch - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A053a0