

View Online at <https://aerobasegroup.com/nsn/5930-00-501-1787>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.370 inches and 0.380 inches

**Overall Height:**

0.563 inches

**Body Length:**

Between 0.765 inches and 0.797 inches

**Body Width:**

Between 0.234 inches and 0.266 inches

**Body Height:**

Between 0.343 inches and 0.375 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.088 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.172 inches and 0.192 inches

**Actuator Height:**

Between 0.035 inches and 0.045 inches

**Actuator Free Position Height:**

Between 0.315 inches and 0.345 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

B-52, c-135, c-130, c-5 aircraft

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

150.0 grams

**Actuator Movement:**

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0