NSN 5930-00-501-1787

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-1787

Body	Style:
------	--------

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.370 inches and 0.380 inches

Overall Height:

0.563 inches

Body Length:

Between 0.765 inches and 0.797 inches

Body Width:

Between 0.234 inches and 0.266 inches

Body Height:

Between 0.343 inches and 0.375 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.088 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.172 inches and 0.192 inches

Actuator Height:

Between 0.035 inches and 0.045 inches

Actuator Free Position Height:

Between 0.315 inches and 0.345 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

B-52, c-135, c-130, c-5 aircraft

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

150.0 grams

Actuator Movement:

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

NSN 5930-00-501-1787

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0