# NSN 5930-00-501-1787

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-1787

Body	Style:
------	--------

Hole mounted

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.370 inches and 0.380 inches

**Overall Height:** 

0.563 inches

**Body Length:** 

Between 0.765 inches and 0.797 inches

**Body Width:** 

Between 0.234 inches and 0.266 inches

**Body Height:** 

Between 0.343 inches and 0.375 inches

**Case Material:** 

Plastic

#### **Unthreaded Mounting Hole Diameter:**

Between 0.088 inches and 0.090 inches

**Actuator Style:** 

Round

**Actuator Diameter:** 

Between 0.172 inches and 0.192 inches

**Actuator Height:** 

Between 0.035 inches and 0.045 inches

**Actuator Free Position Height:** 

Between 0.315 inches and 0.345 inches

**Maximum Voltage Rating In Volts:** 

250.0 ac and 30.0 dc

**End Application:** 

B-52, c-135, c-130, c-5 aircraft

**Inclosure Type:** 

Fully enclosed

**Mounting Method:** 

Unthreaded hole

### **Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 

1.0 ounces

**Criticality Code Justification:** 

Feat

**Switch Actuating Force:** 

150.0 grams

#### **Actuator Movement:**

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

# NSN 5930-00-501-1787

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:** 

Weapon system essential

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0