NSN 5930-00-501-2307

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Watertight

Overall Height: 4.188 inches



View Online at https://aerobasegroup.com/nsn/5930-00-501-2307

Overall Width:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.375 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
63743
Knob Manufacturer Part Number:
13761-98-5
Longest Horizontal Distance Between Mounting Centers:
6.250 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
1 single section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
500.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes single section front

NSN 5930-00-501-2307

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0