

View Online at <https://aerobasegroup.com/nsn/5930-00-501-2402>

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 1.995 inches and 2.005 inches

Shaft Diameter:

0.245 inches single actuator and 0.255 inches single actuator

Shaft Length:

0.870 inches single actuator and 0.880 inches single actuator

Overall Diameter:

Between 1.933 inches and 1.943 inches

Nonturn Device Radius:

0.495 inches at 6: 00 o'clock and 0.505 inches at 6: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

150.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0