NSN 5930-00-501-2563



Rotary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-501-2563
Hazardous Locations/environmental Protection:
Explosion proof
Overall Height:
5.438 inches
Overall Width:
5.688 inches
Shaft Length:
1.125 inches single actuator
Unthreaded Mounting Hole Diameter:
0.438 inches single mounting facility
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
2.875 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.875 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
1 each section front
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
600.0 ac at sea level
Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.312 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-00-501-2563

Rotary Switch - Page 2 of 2



20.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0