

View Online at <https://aerobasegroup.com/nsn/5930-00-501-2563>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

5.438 inches

Overall Width:

5.688 inches

Shaft Length:

1.125 inches single actuator

Unthreaded Mounting Hole Diameter:

0.438 inches single mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.875 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.875 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

1 each section front

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.312 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0