## NSN 5930-00-501-2569

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-2569

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 5.435 inches **Overall Height:** 1.875 inches **Overall Width:** 1.625 inches First Flat Length: 0.375 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 2.250 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 3 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-501-2569

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load ac at sea level
Precious Material And Location:
Contacts and rotor blade surfaces silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0