NSN 5930-00-501-3028

Rotary Switch - Page 1 of 2

Thread Length:



View Online at https://aerobasegroup.com/nsn/5930-00-501-3028

0.375 inches single mounting facility
Overall Length:
5.874 inches
Overall Height:
1.312 inches
Overall Width:
1.062 inches
First Flat Length:
0.375 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.218 inches single actuator
Shaft Length:
0.812 inches single actuator
Nonturn Device Radius:
0.531 inches at 3: 00 o'clock
Individual Section Quantity:
6
Nonturn Device Type:
3,6
Slotted bushing at 3: 00 o'clock
Slotted bushing at 3: 00 o'clock
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility Thread Size:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 285.0 degrees from nonturn device single actuator
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 285.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity:
Slotted bushing at 3: 00 o'clock Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 6th section front Throw Quantity: 9 5th section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Shaft Flat/slot Angular Location: 285.0 degrees from nonturn device single actuator Switch Actuator Indexing Position Quantity: 6 single actuator

Contact Switching Action:

Makes before breaks 6th section front

Tab, solder lug

NSN 5930-00-501-3028

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Special Features:

Two dummy terminals one located on rear section 3 and one on front section 6

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0