## NSN 5930-00-501-3028

Rotary Switch - Page 1 of 2

Thread Length:



View Online at https://aerobasegroup.com/nsn/5930-00-501-3028

0.375 inches single mounting facility
Overall Length:
5.874 inches
Overall Height:
1.312 inches
Overall Width:
1.062 inches
First Flat Length:
0.375 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.218 inches single actuator
Shaft Length:
0.812 inches single actuator
Nonturn Device Radius:
0.531 inches at 3: 00 o'clock
Individual Section Quantity:
6
Nonturn Device Type:
Homain Bevice Type.
Slotted bushing at 3: 00 o'clock
Slotted bushing at 3: 00 o'clock
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility  Thread Size:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility  Thread Size:  0.375 inches single mounting facility
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility  Thread Size:  0.375 inches single mounting facility  Shaft Flat/slot Angular Location:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility  Thread Size:  0.375 inches single mounting facility  Shaft Flat/slot Angular Location:  285.0 degrees from nonturn device single actuator
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility  Thread Size:  0.375 inches single mounting facility  Shaft Flat/slot Angular Location:  285.0 degrees from nonturn device single actuator  Switch Actuator Indexing Position Quantity:
Slotted bushing at 3: 00 o'clock  Switch Contact Basic Design:  Nonpile-up symmetrical  Pole Quantity:  1 6th section front  Throw Quantity:  9 5th section rear  Mounting Method:  Threaded bushing single mounting facility  Thread Size:  0.375 inches single mounting facility  Shaft Flat/slot Angular Location:  285.0 degrees from nonturn device single actuator  Switch Actuator Indexing Position Quantity:  6 single actuator

**Contact Switching Action:** 

Makes before breaks 6th section front

Tab, solder lug

## NSN 5930-00-501-3028

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Special Features:** 

Two dummy terminals one located on rear section 3 and one on front section 6

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0