## NSN 5930-00-501-3795

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-3795

| Body Style:   |
|---|
| Hole mounted  |
| Overall Length:   |
| 1.812 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.520 inches  |
| Overall Height:   |
| 0.594 inches  |
| Overall Width:  |
| 0.500 inches  |
| Body Length:  |
| 1.250 inches  |
| Body Width:   |
| 0.500 inches  |
| Body Height:  |
| 0.500 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.101 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.312 inches  |
| Actuator Length:  |
| 0.250 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.094 inches  |
| Actuator Width:   |
| 0.297 inches  |
| Actuator Free Position Height:  |
| 0.187 inches  |
| Maximum Voltage Rating In Volts:  |
| 250.0 ac and 30.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Unthreaded hole   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, two positions momentary single switch unit          |
| Switch Release Force:   |
| 4.0 ounces  |
| Switch Actuating Force:   |

12.0 ounces

## NSN 5930-00-501-3795

Sensitive Switch - Page 2 of 2



| Δ | ctu | ator | Mov  | ıρm | Δn | +  |
|---|-----|------|------|-----|----|----|
| ~ | υιu | awı  | IVIO | ven |    | ш. |

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

10.000 amperes inductive dc and 10.000 amperes inductive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0