## NSN 5930-00-501-3795

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-3795

Body Style:
Hole mounted
Overall Length:
1.812 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.520 inches
Overall Height:
0.594 inches
Overall Width:
0.500 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.101 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.312 inches
Actuator Length:
0.250 inches
Actuator Style:
Rectangular
Actuator Height:
0.094 inches
Actuator Width:
0.297 inches
Actuator Free Position Height:
0.187 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:

12.0 ounces

## NSN 5930-00-501-3795

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	Mov	ıρm	Δn	+
~	υιu	awı	IVIO	ven		ш.

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

10.000 amperes inductive dc and 10.000 amperes inductive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0