

View Online at <https://aerobasegroup.com/nsn/5930-00-501-3849>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.437 inches single mounting facility

**Overall Length:**

5.251 inches

**First Flat Length:**

0.500 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

1.750 inches single actuator

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

1.188 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 3rd section rear

**Throw Quantity:**

3 1st section rear

**Mounting Method:**

Threaded stud single mounting facility

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.125 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 1st section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0