

View Online at <https://aerobasegroup.com/nsn/5930-00-501-3905>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant and shock resistant

**Overall Length:**

2.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.812 inches

**Overall Height:**

1.937 inches

**Overall Width:**

0.750 inches

**Body Length:**

1.438 inches

**Body Width:**

0.750 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.875 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

440.0 ac and 30.0 dc

**Mounting Surface To Terminal End Distance:**

1.062 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes motor dc and 4.200 amperes resistive ac and 3.000 amperes inductive ac and 1.500 amperes motor ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0