NSN 5930-00-501-3905

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-501-3905

| Body Style: |
|---|
| Hole mount |
| Hazardous Locations/environmental Protection: |
| Corrosion resistant and shock resistant |
| Overall Length: |
| 2.125 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.812 inches |
| Overall Height: |
| 1.937 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 1.438 inches |
| Body Width: |
| 0.750 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.240 inches |
| Actuator Height: |
| 0.875 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Maximum Voltage Rating In Volts: |
| 440.0 ac and 30.0 dc |
| Mounting Surface To Terminal End Distance: |
| 1.062 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded hole |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes motor dc and 4.200 |
| amperes resistive ac and 3.000 amperes inductive ac and 1.500 amperes motor ac |
| Precious Material And Location: |
| Contacts silver |

3 tab w/screw

Terminal Type And Quantity:

NSN 5930-00-501-3905 Toggle Switch - Page 2 of 2



| _ | | | | |
|---|-----|-----|---|------|
| c | hο | .1+ | | ife: |
| J | 116 | | _ | HG. |

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0