

View Online at <https://aerobasegroup.com/nsn/5930-00-502-5964>

**Inside Diameter:**

0.125 inches all connections

**Overall Length:**

2.500 inches

**Body Length:**

2.500 inches

**Overall Diameter:**

3.500 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Mounting Facility Centers:**

4.250 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between 32.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

10.00 pounds per square inch

**Thread Size:**

0.125 inches all pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Threaded hole

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.15/+0.50 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0