## NSN 5930-00-503-1861

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-503-1861 **Body Style:** Hole mounted **Actuator Length:** 1.781 inches **Actuator Style:** Roller arm **Actuator Free Position Height:** 1.532 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.125 inches **Housing Height:** 1.250 inches **Housing Length:** 2.500 inches **Housing Width:** 1.250 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.625 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 1.375 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc **Inclosure Type:** Hermetically sealed **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Switch Actuating Force:** 64.0 ounces **Actuator Movement:** Between 0.100 pretravel inches and 0.281 overtravel inches and 0.040 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes inductive ac **Terminal Type And Quantity:** 1 connector, receptacle Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5930-00-503-1861** Sensitive Switch - Page 2 of 2



Fiig:

A053a0