# NSN 5930-00-503-1865

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-503-1865

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.749 inches

#### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.625 inches

#### First Flat Length:

0.375 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.875 inches single actuator

# Shaft Length:

0.250 inches single actuator

## Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section rear

#### **Throw Quantity:**

8 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

8 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-503-1865

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 500.0 milliamperes resistive load ac at sea level Precious Material And Location:

Contacts and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0