NSN 5930-00-503-2165

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-503-2165

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
7.906 inches
Overall Height:
3.062 inches
Overall Width:
3.250 inches
Actuator Style:
Round
Actuator Diameter:
0.625 inches
Actuator Height:
0.593 inches
Actuator Free Position Height:
1.781 inches
Housing Height:
3.062 inches
Housing Length:
6.125 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
5.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.375 inches
Maximum Voltage Rating In Volts:
440.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Actuator Movement:
Between 0.310 pretravel inches and 0.158 overtravel inches and 0.035 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
0.500 amperes resistive dc and 1.500 amperes resistive ac
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a

NSN 5930-00-503-2165

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0