## NSN 5930-00-503-2165

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-503-2165

## **Body Style:**

Hole mounted

#### Hazardous Locations/environmental Protection:

Watertight

## **Overall Length:**

7.906 inches

#### **Overall Height:**

3.062 inches

#### **Overall Width:**

3.250 inches

#### Actuator Style:

Round

## Actuator Diameter:

0.625 inches

#### **Actuator Height:**

## 0.593 inches

## Actuator Free Position Height:

1.781 inches

#### **Housing Height:**

3.062 inches

#### Housing Length:

6.125 inches

#### Housing Width:

3.250 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

5.250 inches

#### Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

2.375 inches

#### Maximum Voltage Rating In Volts:

440.0 ac and 250.0 dc

#### Inclosure Type:

Fully enclosed

#### Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

#### **Actuator Movement:**

Between 0.310 pretravel inches and 0.158 overtravel inches and 0.035 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 1.500 amperes resistive ac

## **Terminal Type And Quantity:**

4 screw

#### Shelf Life:

N/a

# NSN 5930-00-503-2165

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

