## NSN 5930-00-503-2188

Rotary Switch - Page 1 of 2

0.375 inches single mounting facility

Thread Length:

**Overall Height:** 



View Online at https://aerobasegroup.com/nsn/5930-00-503-2188

4.144 inches
Overall Width:
3.625 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
2.188 inches single actuator
Individual Section Quantity:
2
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6503-73437-37
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
30 each section front
Mounting Method:
Mounting Method:  Threaded bushing single mounting facility
_
Threaded bushing single mounting facility
Threaded bushing single mounting facility  Features Provided:
Threaded bushing single mounting facility  Features Provided:  Actuator knob
Threaded bushing single mounting facility  Features Provided:  Actuator knob  Thread Size:
Threaded bushing single mounting facility  Features Provided:  Actuator knob  Thread Size:  0.625 inches single mounting facility
Threaded bushing single mounting facility  Features Provided:  Actuator knob  Thread Size:  0.625 inches single mounting facility  Contact Voltage Rating In Volts:
Threaded bushing single mounting facility  Features Provided:  Actuator knob  Thread Size:  0.625 inches single mounting facility  Contact Voltage Rating In Volts:  28.0 dc at sea level
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity:
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity: 30 single actuator
Threaded bushing single mounting facility  Features Provided:  Actuator knob  Thread Size:  0.625 inches single mounting facility  Contact Voltage Rating In Volts:  28.0 dc at sea level  Switch Actuator Indexing Position Quantity:  30 single actuator  Shaft Type:
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity: 30 single actuator  Shaft Type: Round single actuator
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity: 30 single actuator  Shaft Type: Round single actuator  Terminal Type:
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity: 30 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity: 30 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action:
Threaded bushing single mounting facility  Features Provided: Actuator knob  Thread Size: 0.625 inches single mounting facility  Contact Voltage Rating In Volts: 28.0 dc at sea level  Switch Actuator Indexing Position Quantity: 30 single actuator  Shaft Type: Round single actuator  Terminal Type: Tab, solder lug  Contact Switching Action:  Breaks before makes each section front

10.0 amperes resistive load dc at sea level

## NSN 5930-00-503-2188

Rotary Switch - Page 2 of 2



Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0