# NSN 5930-00-503-3884

Sensitive Switch - Page 1 of 2

20.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-00-503-3884

| Body Style:   |
|---|
| Hole mounted  |
| Hazardous Locations/environmental Protection:                             |
| Dustproof   |
| Overall Length:   |
| 1.945 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches  |
| Overall Height:   |
| 2.250 inches  |
| Overall Width:  |
| 0.705 inches  |
| Body Length:  |
| 1.945 inches  |
| Body Width:   |
| 0.705 inches  |
| Case Material:  |
| Metal   |
| Unthreaded Mounting Hole Diameter:  |
| 0.139 inches  |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| 0.320 inches  |
| Actuator Height:  |
| 0.410 inches  |
| Actuator Free Position Height:  |
| 1.625 inches  |
| Maximum Voltage Rating In Volts:  |
| 28.0 dc   |
| Inclosure Type:   |
| Fully enclosed  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Thread Size:  |
| 0.469 inches  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit           |
| Switch Release Force:   |
| 6.0 ounces  |
| Switch Actuating Force:   |

# NSN 5930-00-503-3884

Sensitive Switch - Page 2 of 2



### **Actuator Movement:**

Between 0.065 pretravel inches and 0.188 overtravel inches and 0.010 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 2.000 amperes lamp dc and 4.000 amperes motor dc

## **Special Features:**

Hi-temperature limit switch

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

3 threaded stud

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A053a0