

View Online at <https://aerobasegroup.com/nsn/5930-00-503-3884>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.945 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

2.250 inches

Overall Width:

0.705 inches

Body Length:

1.945 inches

Body Width:

0.705 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Round

Actuator Diameter:

0.320 inches

Actuator Height:

0.410 inches

Actuator Free Position Height:

1.625 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.065 pretravel inches and 0.188 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 2.000 amperes lamp dc and 4.000 amperes motor dc

Special Features:

Hi-temperature limit switch

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0