NSN 5930-00-503-4351

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-503-4351

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.952 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.875 inches
Overall Width:
0.703 inches
Body Length:
1.952 inches
Body Width:
0.703 inches
Body Height:
0.828 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Free Position Height:
0.625 inches
Maximum Voltage Rating In Volts:
115.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
13.0 ounces
Actuator Movement:
Between 0.015 pretravel inches and 0.005 overtravel inches and 0.0004 differential inches

NSN 5930-00-503-4351

Sensitive Switch - Page 2 of 2



Contact Load Current Ratio	g At Maximum	Rated Voltage:
----------------------------	--------------	----------------

15.000 amperes resistive ac

Special Features:

High temp, asbestos filled case

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A053a0