

View Online at <https://aerobasegroup.com/nsn/5930-00-504-6094>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.950 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Height:

1.275 inches

Overall Width:

0.700 inches

Body Length:

1.950 inches

Body Width:

0.700 inches

Body Height:

0.920 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.112 inches

Actuator Free Position Height:

Between 0.600 inches and 0.630 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Helicopter iroquois uh-1

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

0.085 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 screw

Specification Data:

96906-ms25008 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0