

View Online at <https://aerobasegroup.com/nsn/5930-00-504-6094>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.950 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Overall Height:**

1.275 inches

**Overall Width:**

0.700 inches

**Body Length:**

1.950 inches

**Body Width:**

0.700 inches

**Body Height:**

0.920 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.094 inches

**Actuator Height:**

0.112 inches

**Actuator Free Position Height:**

Between 0.600 inches and 0.630 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Helicopter iroquois uh-1

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

20.0 ounces

**Actuator Movement:**

0.085 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes motor dc

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 screw

**Specification Data:**

96906-ms25008 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0