NSN 5930-00-504-6456

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-504-6456

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|--|
| 1.000 inches |
| Body Length: |
| 1.938 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 0.828 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Free Position Height: |
| 1.547 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 dc |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 13.0 ounces |
| Actuator Movement: |
| Between 0.015 pretravel inches and 0.219 overtravel inches and 0.002 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |
| |