## NSN 5930-00-504-6551

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-504-6551

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.625 inches **Overall Height:** 1.312 inches **Overall Width:** 1.250 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.875 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Operating Tempurature Range:** -25.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 2 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Rotor Through Connection Quantity:** 1 single section **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator

**Terminal Type:** Tab, solder lug

## NSN 5930-00-504-6551

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes single section rear
<b>Switch Actuator Positioning Increment:</b>
60.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Special Features:
Shaft has threaded cross-hole
Precious Material And Location:
Contacts and rotor silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0