

View Online at <https://aerobasegroup.com/nsn/5930-00-504-6584>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.491 inches

Overall Height:

1.484 inches

Overall Width:

1.438 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

2.250 inches single actuator

Nonturn Device Radius:

0.438 inches at 9: 00 o'clock

Individual Section Quantity:

2

Knob Manufacturer Code:

71590

Knob Manufacturer Part Number:

P-120

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

6.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.5 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0